

Jet Spot2

150W moving spot with white LED source



Jet Spot2 is a LED spot luminaire designed to deliver a stunning light level for its size and price. Ideal both for installation and for rental, the **Jet Spot2** focuses on maximising the light output from its LED source to deliver a crisp, even beam from a compact size.

MAIN FEATURES

- Ultra-efficient 150W 8.000 K white LED source
- Fixed 20° beam angle
- Extensive effects including one colour wheel, rotating gobo wheel, static gobo wheel, prism and focus

VERSIONS

Code	Housing
JETSPOT2BK	Black
JETSPOT2WH	White

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 150W high-power white LED
- CCT: 8.000K
- Luminous flux: 7'400lm
- Lux: 8'900lx @3 m
- Lux: 810lx @10 m
- CRI: 78
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 20°
- Focus: motorised

COLOUR SYSTEM

- Colour wheel: 8 colour filters

DYNAMIC EFFECTS

- Rotating gobos: 7 rotating gobos + open, interchangeable, indexing
- Gobo size: outer: 24,2 mm - image: 20 mm - thickness: 0,3 mm
- Fixed gobos: 8 fixed gobos + open
- Circular prism: 3f with bi-directional rotation, indexing
- Auto mode: built-in programs with execution speed adjustment

BODY

- Pan angle: 540°
- Tilt angle: 270°
- Pan/Tilt resolution: 8 / 16-bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with high-resistance polycarbonate cover
- Body colour: black, white finishing available

CONTROL

- Protocols: DMX512, RDM
- DMX channels: 12 / 15channel
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: -10° ~ +45°

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 225W
- Max power consumption (at 120V): 226W
- Output (at 230V): 16 units on a single power line
- Output (at 120V): 8 units on a single power line

PHYSICAL

- IP rating: 20
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: XLR 3p + 5p IN/OUT connectors
- Power connection: Seetronic powerCON IN/OUT connectors
- Dimensions (WxHxD): 308x436x230mm
- Weight: 13,7kg

CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM

ACCESSORIES & RELATED PRODUCTS

• 9313FCAL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, SETSAC3FCA socket, L.3 m
• 9333FCAL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, SETSAC3FCA socket, L.3 m
• 938025L03	3x2.5mm TH07 Cable, 20A SETSAC3FCA, 20A SETSAC3FCB, L. 3m
• C6016B	Quick-trigger slim clamp, 250Kg load, 48-51mm tubes, M10 bolt incl, Black

• FCLJET2	Flight case per 4 pcs of JETBEAM2 / JETSPOT2
• RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
• TOUR53413L03	Dmx cable HC5340. CANS3MXX XLR 3p->CANS3FXX XLR (f) 3p, L.3m
• TOUR53415L03	Dmx cable HC5340. CANS5MXX XLR 5p->CANS5FXX XLR (f) 5p, L.3m