

# Jet Spot3

240W moving spot with White LED source



**Jet Spot3** is a LED spot luminaire designed to deliver a stunning light level for its size and price. Ideal both for installation and for rental, the **Jet Spot3** focuses on maximising the light output from its LED source to deliver a crisp, even beam from a compact size.

## MAIN FEATURES

- Ultra-efficient 240W 7.000 K White LED source
- Fixed 20° beam angle
- Extensive effects including 2 colour wheels, rotating gobo wheel, static gobo wheel, prism, linear frost, iris and focus

## VERSIONS

Code	Housing
JETSPOT3BK	Black
JETSPOT3WH	White

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 240W high-power white LED
- CCT: 7.500K
- Luminous flux: 12'459lm
- Lux: 13'389lx @3 m
- Lux: 1'205lx @10 m
- CRI: 78
- Source life expectancy: > 30.000 h

### OPTICS

- Beam angle: 20°
- Lens diameter: 74mm
- Lens type: high-quality glass lens optics
- Focus: motorised

### COLOUR SYSTEM

- Colour wheel: 7 colour filters on two colour wheels

### DYNAMIC EFFECTS

- Rotating gobos: 7 rotating gobos + open, interchangeable, indexing
- Gobo size: outer: 26,7 mm - image: 23 mm - thickness: 0,3 mm
- Fixed gobos: 8 fixed gobos + open, interchangeable
- Gobo size: outer: 29,6 mm - image: 23 mm - thickness: 0,5 mm
- Circular prism: 3f with bi-directional rotation, indexing
- Frost: linear 0 - 100% frost filter
- Iris: 5 ~ 100% motorised iris
- Auto mode: built-in programs with execution speed adjustment

### BODY

- Pan angle: 540°
- Tilt angle: 260°
- Pan/Tilt resolution: 16-bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with high-resistance polycarbonate cover
- Body colour: black, white finishing available

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 17 / 19channel
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 0 ~ 30 Hz, electronic
- Display battery: self-charging battery backup
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 316W
- Max power consumption (at 120V): 322W
- Output (at 230V): 12 units on a single power line
- Output (at 120V): 6 units on a single power line

### PHYSICAL

- IP rating: 20
- Cooling: active, silent operation
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 3p + 5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- Dimensions (WxHxD): 355x500x257mm
- Weight: 17,3kg

### CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM, cTUVus, FCC

## ACCESSORIES & RELATED PRODUCTS

▪ 9513FCAL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FCA socket, L.3m
▪ 9533FCAL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FCA socket, L.3m
▪ 958025L03	3x2.5mm TH07 Cable, 20A 3p PwCon FCA, 20A 3p PwCon FCB, L. 3m
▪ C6016B	Quick-trigger slim clamp, 250Kg load, 48-51mm tubes, M10 bolt incl, Black

▪ FCLJS3	Flight case for 2 pcs of JETSPOT3
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
▪ TOUR53413L03	Dmx cable HC5340. CANS3MXX XLR 3p->CANS3FXX XLR (f) 3p, L.3m
▪ TOUR53415L03	Dmx cable HC5340. CANS5MXX XLR 5p->CANS5FXX XLR (f) 5p, L.3m
▪ OS25	Quick-Lock omega bracket