

LumiPar 12IP

12x9W RGBW compact IP65 LED PAR



LumiPar 12IP is a bright and flexible IP LED PAR made for concerts, theatres and to perform as an architectural accent light for outdoor events. The housing in die-cast aluminium is designed to feature both as a robust workhorse and being totally fan-free allows for total silence during operation.

MAIN FEATURES

- IP65 die-cast aluminium housing
- 12x9W RGBW LED PAR
- Fan-free and flicker-free
- Filter frame included

VERSIONS

| Code | Beam angle |
|----------------|------------|
| LUMIPAR12IP20D | 20° |
| LUMIPAR12IP45D | 45° |

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 12x9 W RGBW LEDs
- Luminous flux: (25°) 3'900 lm - (45°) 6'700
- Lux: (25°) 2'535 lx @3 m full
- Lux: (45°) 1'154 lx @3 m full
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: available in 25° or 45°
- Field angle: 36° or 60°
- COLOUR SYSTEM
- Colour mixing: RGBW / FC
- White presets: 3.000 K ~ 10.000 K
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 11 channel
- Display: black OLED touch display
- Firmware upgrade: yes, via USB - DMX interface (UPBOXPRO/UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 0 - 30 Hz, electronic
- Display battery: self-charging battery backup
- Operating temperature: -20° ~ +45°
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 110 W
- Max power consumption (at 120V): 110 W
- Output (at 230V): 33 units on a single power line
- Output (at 120V): 18 units on a single power line
- Inrush current: 110VAC/20.5A, 230VAC/24.8A

PHYSICAL

- IP rating: 65 for temporary outdoor application, not for fixed installations
- IK rating: 07
- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerCON TRUE IP65 IN/OUT
- Dimensions (WxHxD): 305x326x177 mm
- Weight: 6,2 kg

CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM

ACCESSORIES & RELATED PRODUCTS

| | | | |
|-----------------|--|---------------|---|
| ▪ 9313FXWL03 | Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, SETSAC3FX socket, L.3 m | ▪ C6002B | Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black |
| ▪ 9333FXWL03 | Ass. 3x2.5mm TH07 cable, SHUKO plug, SETSAC3FX socket, L.3m | ▪ INF53415L03 | Dmx cable HC5340. SETMC5MXXB XLR 5p->SETMC5FXXB XLR (f) 5p L.3m |
| ▪ 938225L03 | 3x2.5mm TH07 Cable, 16A SETSAC3MX, 16A SETSAC3FX, L. 3m | ▪ RSR0630B | Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black |
| ▪ ARCLUMIL25D45 | Optic lens 25°, D.45mm | ▪ UPBOX1U | Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT |