

# Jet Spot1

18W moving spot with white LED source



**Jet Spot1** is an extremely compact LED spotlight designed to deliver a bright, even beam from the smallest footprint possible. Ideal where space is an issue, the **Jet Spot1** simply offers the best value for money in its segment with a light output far exceeding expectations. All packaged in a compact size and offered at an affordable price.

## MAIN FEATURES

- Ultra-efficient 18W white LED with 16° glass optics, to deliver an outstanding light level and even beam
- Compact size for use where space is an issue - including clubs, bars, and events
- 9 colours and 9 gobos giving a vast range of effect options

## VERSIONS

Code	Housing
JETSPOT1BK	Black
JETSPOT1WH	White

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 18W high-power white LED
- CCT: 7.000K
- Luminous flux: 1'288lm
- Lux: 2'533lx @3 m
- Lux: 227,97lx @10 m
- CRI: 73
- Source life expectancy: > 30.000 h

### OPTICS

- Beam angle: 16°
- Lens type: high-quality glass lens optics

### COLOUR SYSTEM

- Colour wheel: 9 colour filters

### DYNAMIC EFFECTS

- Fixed gobos: 9 fixed gobos + open
- Auto mode: built-in programs with execution speed adjustment
- Sound mode: music activation through internal microphone and sensitivity control

### BODY

- Pan angle: 540°
- Tilt angle: 270°
- Pan/Tilt resolution: 8 / 16-bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with high-resistance polycarbonate cover
- Body colour: black, white finishing available

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 8 / 10channel
- Wireless Control: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

## ACCESSORIES & RELATED PRODUCTS

▪ 9313FCAL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, SETSAC3FCA socket, L.3 m
▪ 9333FCAL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, SETSAC3FCA socket, L.3 m
▪ 938025L03	3x2.5mm TH07 Cable, 20A SETSAC3FCA, 20A SETSAC3FCB, L. 3m
▪ C6016B	Quick-trigger slim clamp, 250Kg load, 48-51mm tubes, M10 bolt incl, Black
▪ FCLJET1	Flight case for 8 pcs JETBEAM1 / JETSPOT1

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 0 ~ 30 Hz, electronic
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 40,6W
- Max power consumption (at 120V): 39,7W
- Output (at 230V): 67 units on a single power line
- Output (at 120V): 37 units on a single power line

### PHYSICAL

- IP rating: 20
- Cooling: active, silent operation
- Suspension and fixing: any position with quick-lock omega brackets
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 5p IN/OUT connectors
- Power connection: Seetronic powerCON IN/OUT connectors
- Dimensions (WxHxD): 210x308x170mm
- Weight: 4,2kg

### CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM

▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
▪ TOUR53415L03	Dmx cable HC5340. CANS5MXX XLR 5p->CANS5FXX XLR (f) 5p, L.3m
▪ WIFIU5B	USB Wi-Fi transceiver, compatible with WIFIBOX and WDBOX
▪ WIFIBOX	DMX controller interface, Wi-Fi/DMX IN, Wi-Fi / DMX OUT
▪ WDBOX	Wireless DMX Transceiver, IN/OUT 3-pin XLR, distance 200m, 2.4 GHz, 0.6 kg
▪ UPBOX1U	Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT