

# Diamond 19CC

19x15W moving LED wash RGBW FC

ORDER CODE: **DIAMOND19CC**



**Diamond 19CC** is a pure wash light version of the Diamond 19. Retaining the massive 7,5° - 41,4° zoom, even beam and truly fantastic colour range but removing the individual control of each pixel. When the budget won't quite stretch to the fully featured **Diamond 19**, the show can still look stunning with the **Diamond 19CC**.

## MAIN FEATURES

- 19x15W RGBW FC LEDs
- 7,5° - 41,4° zoom
- Dual LED zone control for basic 'eye-candy' effects
- CT channel with white emulation: 2.800 K - 9.000 K
- Liquid cooling system for minimal noise

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 19x15W RGBW LED
- Luminous flux: (7,5°) 2'701 lm - (41,4°) 3'875lm @full
- Lux: (7,5°) 5'411 lx - (41,4°) 831lx @5 m full
- Source life expectancy: > 50.000 h

### OPTICS

- Zoom: 7,5° - 41,4° motorised linear zoom
- Lens type: honeycomb gapless plano-convex optics

### COLOUR SYSTEM

- Colour mixing: RGBW / FC
- CCT: CCT control through dedicated DMX channel
- White presets: 2800 K ~ 9000K
- Colour wheel: virtual colour wheel with macros

### DYNAMIC EFFECTS

- FX generator: 2 sections ring control

### BODY

- Pan angle: 630°
- Tilt angle: 265°
- Pan/Tilt resolution: 8 / 16-bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with high-resistance polycarbonate cover
- Body colour: black

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 14/15/16/26channel
- Pixel control: ring control
- Wireless Control: optional, wireless solution receiver
- RDM: RDM for remote monitoring and settings
- Display: LCD high resolution colour display

- Firmware upgrade: yes, via USB - DMX interface (UPBOX2) not included
- Hibernation: power safe mode when lost DMX
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 25 Hz, electronic
- Display battery: self-charging battery backup
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 275W
- Output (at 230V): 6 units on a single power line

### PHYSICAL

- IP rating: 20
- Cooling: combination of heat pipe cooling system and low noise fan
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 3p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- Dimensions (WxHxD): 338x449x235mm
- Weight: 11kg

### CERTIFICATIONS / APPROVALS


- Certifications / Approvals: CE, UKCA, RCM

## ACCESSORIES & RELATED PRODUCTS

▪ 9513FCAL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FCA socket, L.3m	▪ TOUR53415L03	Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m
▪ 9533FCAL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FCA socket, L.3m	▪ WSA40501	WDMX, antenna 2.4Ghz 2dBi omnidirectional, folding, SMA-male, indoor
▪ 958025L03	3x2.5mm TH07 Cable, 20A 3p PwCon FCA, 20A 3p PwCon FCB, L. 3m	▪ WR24ANG5	WIRELESS SOLUTION, nano RX DMX 3.3V/5V-18V MCX
▪ C6016B	Quick-trigger slim clamp, 250Kg load, 48-51mm tubes, M10 bolt incl, Black	▪ FCL40019	Flight case for 4x STARK400 or DIAMOND19
▪ OS24	Quick-lock omega bracket.	▪ FCLDIAMOND19	Flight case for 4pcs of DIAMOND19
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black	▪ FCLDIAMOND19E	Flight case for 4pcs of DIAMOND19, made in UE
▪ TOUR53413L03	Dmx cable HC5340. CANC3MXX XLR 3p->CANC3FXX XLR (f) 3p, L.3m	▪ FSHLW01	1U Foam shell compatible with DIAMOND19, STARK400
		▪ UPBOX2	Firmware uploader kit, USB IN, 3-pin XLR DMX OUT


## PRESET FULL ON

Beam angle 50%: 7,5°




## PRESET FULL ON

Beam angle 50%: 41,4°



## TECHNICAL DRAWINGS



Visit our website  
for specifications and  
tech documentations

