

Tabled W

Revolutionary tunable white event battery table lamp



Tabled W is an ingenious product which offers beautiful table lighting for events whilst keeping with the atmosphere in the room. Based on a stunning aesthetic design, it is not only a stylish centerpiece but fast to deploy and easy to use. With local control it can either act as a standalone table light or part of a spectacular event lighting package.

MAIN FEATURES

- Battery powered for fast deployment and accurate control
- Tunable white LED source with 360° coverage for standard catering round tables of 1.8m
- Available in a TABLED-W PACK featuring 4 lights with accessories in an ABS case

TABLED-WPACK

- 4 pcs TABLEDCWH/CMR
- 4 pcs base disks
- 2 pcs extensions (TABLEDEXT)
- 1 pcs IR controller (PRL-IRC)
- 1 pcs ABS with recharging system
- 1 pcs IEC power cable

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 6x1 W + 6x1W Warm White + Cold White LEDs
- CCT: 3.200 K - 5.600K
- CRI: 80
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 360° designed to light up standard 160/180 cm ceremony tables

COLOUR SYSTEM

- Colour mixing: tunable white

DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of colour

BODY

- Hardware on-board: magnetic base
- Body: sturdy die-cast aluminium body
- Body colour: mirror finishing
- Other: 1 x TABLEDDSK22W and 1x1 recharger included inside single unit box

CONTROL

- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- IR: infrared sensor controlled by remote (included in the pack, not included in single unit)

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: 0° ~ +35°

ELECTRICAL

- Mains power supply: DC 24 V, 1 A, 24 W
- Max power consumption: 9W

BATTERY

- Battery: 2.200 m Ah - 14,8V lithium
- Estimated battery life in single colour mode up to: W: 14h - A: 14,5h
- Estimated battery life in full-mode up to: 8h
- Re-charge connection: power supply
- Re-charge time: 4h/max
- Battery status: LED battery status indicator

PHYSICAL

- IP rating: 30
- Suspension and fixing: magnetic base to attach on every metal surface
- Data connection: infrared sensor controlled
- Dimensions (WxHxD): 140x307x220mm
- Weight: 1,16kg

CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM

ACCESSORIES & RELATED PRODUCTS

- | | |
|-------------|---|
| ▪ C6002B | Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black |
| ▪ RSR0630B | Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black |
| ▪ TABLEDMAG | Big magnet for TABLED |
| ▪ TABLEDEXT | Extension tube for Tabled |
| ▪ PRL-IRC | RGBWA IR controller, 29 buttons, manual/static colours, auto programs, fade |

- | | |
|-----------------|---|
| ▪ TABLEDDSK22W | White disk for TABLED, D 220 mm |
| ▪ TABLEDDSK22MT | Transparent disk with magnet for TABLED, D 220 mm |
| ▪ TABLEDDSK28MW | White disk with magnet for TABLED, D 280 mm |
| ▪ TABLEDDSK40MW | White disk with magnet for TABLED, D 400 mm |
| ▪ UPBOX1U | Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT |
| ▪ TABUPBOX1 | Interface used between UPBOX1U and TABLED for make firmware upgrade |