

# Lumipix 12TRIIP

12x3W RGB/FC high-efficiency LED IP rated

ORDER CODE: **LUMIPIX12TRIIP**

# TRIBE



**Lumipix 12TRIIP** is a 1 m long outdoor linear colour changer equipped with 12 high-efficiency RGB / FC LED (3 W each). The control system is fully customisable allowing pixel control and independent selection of each LED from 3 to 36 channels. **Lumipix 12TRIIP** offers advanced possibilities in effect generation as LED video or sound activated arrays.

## MAIN FEATURES

- 12x3W RGB/FC high-efficiency LED
- Section control of the LED plate generating a wide range of dynamic effects
- IP67 rated
- Flicker-free operations

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 12x3W RGB LEDs
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 16°
- Field angle: 30°

### COLOUR SYSTEM

- Colour mixing: RGB / FC
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

### DYNAMIC EFFECTS

- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512
- DMX channels: 3 / 4 / 6 / 7 / 9 / 12 / 18 / 36 channel
- Pixel control: pixel2pixel control
- Display: LCD display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 28 Hz, electronic
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 40W
- Output (at 230V): 16 units on a single power line

### PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: moulded IP signal IN/OUT connectors
- Power connection: moulded IP power IN connector
- IP rating: 67
- Dimensions (WxHxD): 993x173x100 mm
- Weight: 6,5 kg

## ACCESSORIES & RELATED PRODUCTS

- |            |   |           |  |
|------------|---|-----------|--|
| ▪ ARCAD1   | Adaptor cables to link ARCLD projectors to other Prolights IP fixtures.   | ▪ BAG030L | Nylon bag for LUMIPIX bars, 2(int) compartments, dim.1080x180x180 mm |
| ▪ ARCEXDC3 | IP67 DMX extension cable, comp. with outdoor (IP) ARCLD projectors        | ▪ UPBOX1U | Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT             |
| ▪ ARCEXAC3 | IP67 power extension cable, compatible with outdoor (IP) ARCLD projectors |           |  |