

# Accent 1Q

10W RGBW/FC CREE LED high-density accent light

ORDER CODE: **ACCENT1Q**

TRIBE



**Accent 1Q** is an high-density accent light with narrow optic design, conceived to house an high power CREE 10W RGBW/FC LED source in an unprecedented pocket shape. The colour calibration system based on RGBW multi-chip source, offers an advanced chromatic generation and a full control over colour saturation and temperature.

## MAIN FEATURES

- 10W RGBW/FC CREE LED
- 10° narrow beam angle ideal for accent lighting
- Compact and lightweight (900 g)
- Electronics and UI on-board

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 10W RGBW LED
- Luminous flux: 279 lm
- Lux: 357 lx @3 m full
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 10°
- Field angle: 12°

### COLOUR SYSTEM

- Colour mixing: RGBW / FC
- White presets: 3.200 K ~ 10.000 K
- Colour wheel: virtual colour wheel with macros

### DYNAMIC EFFECTS

- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 10 channel
- Display: LCD display
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Operating temperature: -20° ~ +45°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 14,6W
- Max power consumption (at 120V): 15,4W

### PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: moulded IP power IN connector
- IP rating: 30
- Dimensions (WxHxD): 110x67x172 mm
- Weight: 0,89 kg

## ACCESSORIES & RELATED PRODUCTS

- |                 |  |
|-----------------|--|
| ▪ UPBOX1U       | Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT |
| ▪ ARCLUMIL15D45 | Optic lens 15°, D.45mm                                   |

- |                 |                        |
|-----------------|------------------------|
| ▪ ARCLUMIL25D45 | Optic lens 25°, D.45mm |
| ▪ ARCLUMIL40D45 | Optic lens 40°, D.45mm |