

# FlatPar 3Q

3x8W RGBA/FC PAR LED

ORDER CODE: **FLATPAR3Q**

TRIBE



**FlatPar 3Q** is a super-slim LED PAR, conceived to be a multi-purpose wash light which can be used for every kind of event and install with RGBA/FC. **FlatPar 3Q** has been designed with signal and power connections on the sides and a flat bottom, making it very useful for floor applications and as compact and powerful wall-washer. Its round shape and die-cast aluminium housing with tempered glass panel makes **FlatPar 3Q** a nice design tool which can also be used for in-sight applications at every kind of event such as conferences, wedding parties, fashion events and exhibitions.

## MAIN FEATURES

- 3x8W RGBA/FC LED
- Flicker-free operations
- Compact and powerful wall-washer
- Silent operation and HD dimming system

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 3x8W RGBA LEDs
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 25°
- Field angle: 44°
- Lens diameter: 38 mm
- Additional optics: 45° (optional)

### COLOUR SYSTEM

- Colour mixing: RGBA / FC
- White presets: 3.200 K ~ 10.000 K
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

### DYNAMIC EFFECTS

- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment
- Sound mode: music activation through internal microphone and sensitivity control

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512
- DMX channels: 4 / 9 channel
- Display: LED display user interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- IR: infrared sensor controlled by remote
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 28 Hz, electronic
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 25W
- Output (at 230V): 30 units on a single power line

### PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 187x152x187 mm
- Weight: 1,6 kg

## ACCESSORIES & RELATED PRODUCTS

- LUMIPARIRCH RGBWA IR remote controller, manual / auto modes, for LUMIPAR IR series (included)
- ARCLUMIL25D38 Optic lens 25°, D.38mm (included)

- ARCLUMIL45D38 Optic lens 45°, D.38mm
- UPBOX1U Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT