

ComBy FX

Combo laser projector

ORDER CODE: COMBYFX

TRIBE



ComBy FX is a combo effect with laser / LED / strobe source for multi-beam laser projection, motion effects and lounge deco. Thanks to 8 lenses with wide projection angle in combination with an RGBWA LED source, you can create hundreds of multi-coloured effects - in motion and in rotation; a ring composed of 8 white LED reproduces spectacular strobe effects. The laser equipped with red and green diodes, complete the formidable mix of effects. Its concept and versatility make **ComBy FX** suitable for application in clubs, disco and mobile DJ sets.

MAIN FEATURES

- Light source: laser diodes 150 mW 650 nm red + 50 W 532nm green, 8x3 W RGBWA LED, 8x1 W SMD5050 white LED
- Lenses Beam angle: 65°
- Effect: hundreds of multi-coloured effects, in motion and in rotation; a ring composed of 8 white LED reproduces spectacular strobe effects

TECHNICAL SPECIFICATION

- Light source: laser diodes 150mW 650nm red + 50mW 532nm green, 8x3W RGBWA LEDs, 8x1W SMD5050 white LEDs
- LEDs average life span:> 50,000 hours
- Lenses Beam angle: 65°
- Control panel and user interface through LED display (4-digits)
- Auto mode: preset automatic programs with speed control
- DMX mode: 9 channels of operation for the independent control of the play of light, color, strobe effect, laser and motors rotations
- Master/Slave: For the control of several units linked in a chain
- Sound Mode: Switch music via the internal microphone, sensitivity control

- Connections: XLR-3p (signal), VDE plug (power supply)
- Power Supply: AC 100/240V, 50/60Hz
- Average power consumption: 66W
- Power output for connection of multiple units in series: up to 10 projectors at 230V
- Weight: 4.
- 2 kg
- Dimensions (WxHxD): 313x246x315 mm

ACCESSORIES & RELATED PRODUCTS

- C6002B Slim aluminium clamp, 200 kg loading, 48-51 mm tubes, M10 bolt
- RSR0630B Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black

- VDE15SEU Power cable VDE socket, Shuko plug
- TOUR53415L03 Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m