

Polar 500

High power LED strobe

ORDER CODE: **POLAR500**

TRIBE



Polar 500 is a LED strobe engineered to offer a true explosion of light and a range of dynamic effects - all in a unique fixture. The light source is composed of 90 SMD 6.500 K 0,5 W LED allowing for a full-on continuous operation and capable to offer an equal output of conventional 500 W strobe from just one-sixth of the nominal power.

MAIN FEATURES

- 90x0,5 W SMD Cold White LED
- Capability to feature full-on operation like a blinder
- Super-slim design despite its outstanding output
- Comparable to a 500 W strobe

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 90x0.5 W Cold White LEDs
- CCT: 6.000
- Luminous flux: 1'808 lm
- Lux: 59,6 lx @ 3 m
- CRI: 72
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 110 °
- Field angle: 149 °

COLOUR SYSTEM

- Macros: several pre-built pixel macros with adjustable speed

DYNAMIC EFFECTS

- Manual mode: manual adjustment of dimmer and strobe
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

CONTROL

- Protocols: DMX512
- DMX channels: 1 / 4 / 5 / 8 channel
- Pixel control: ring control
- Display: LCD display
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Strobe / shutter: 1 - 28 Hz, electronic
- LED Control: flicker free operation

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 23,5 W
- Max power consumption (at 120V): 23,9 W
- Output (at 230V): 54 units on a single power line
- Output (at 120V): 29 units on a single power line

PHYSICAL

- IP rating: 30
- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- Dimensions (WxHxD): 170x130x170 mm
- Weight: 1,5 kg

CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE

ACCESSORIES & RELATED PRODUCTS

- C6002B Slim aluminium clamp, 200 kg loading, 48-51 mm tubes, M10 bolt
- RSR0630B Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
- VDE15SEU Power cable VDE socket, Shuko plug
- TOUR53415L03 Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m

- LUMIPARIRCH RGBWA IR remote controller, manual / auto modes, for LUMIPAR IR series
- UPBOX1UP5 Firmware uploader kit, USB IN, 5-pin XLR DMX OUT