

EclDisplay DATVW

33W variable white LED Gallery light, with data control (DMX, Dali T6, knob-dimming)



The **EclDisplay** is a range of revolutionary and flexible LED spotlights designed for galleries, commercials and any public venue where an advanced but classy fixture, with several control options, sources and optic versions available to precisely meet any application. The **EclDisplay** DATVW can be set and addressed through RDM, and includes a broad set of on-board input control options: DMX, DALI Type 6 or local knob dimming control. The **EclDisplay** DATVW includes a high-efficiency 33W tunable white, high CRI LED source, with a CCT range from 2,700K to 5,600K, and it is completed with a wide selection of optional profile (zoom and static) or wash lenses, and other optical accessories like louvres and snoots, making it truly a multi-purpose fixture.

MAIN FEATURES

- Data control through RDM, DMX, DALI Type 6 and local knob dimming
- 33W high CRI tunable white LED, from 2,700K to 5,600K, in black and white housing
- Multiple lens options: profile (zoom and static) or wash optics

VERSIONS

Code	Housing
ECLDISPLAYDATVWB	Black
ECLDISPLAYDATVWW	White

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 35 W Tunable White LED
- CCT: 2700K to 5600K
- Luminous flux: 2700K: (profile - 8°) 461 lm - (profile - 10°-20°) 838 lm @20° - (profile - 20°-40°) 833 lm @40° - (wash 25°-50°) 866 lm @50° - (wash 15°-30°) 802 lm @30° lm
- Luminous flux: 5600K: (profile - 8°) 641 lm - (profile - 10°-20°) 1'168 lm @20° - (profile - 20°-40°) 1'153 lm @40° - (wash 25°-50°) 1'183 lm @50° - (wash 15°-30°) 1'122 lm @30°
- Lux: 2700K: (profile - 8°) 1'334 lx - (profile - 10°-20°) 1'344 lx @10°; 426 lx @20° - (profile - 20°-40°) 347 lx @20°; 91 lx @40° - (wash 25°-50°) 134 lx @25°; 49 lx @50° - (wash 15°-30°) 292 lx @15°; 109 lx @30° lx @5 m
- Lux: 5600K: (profile - 8°) 1'807 lx - (profile - 10°-20°) 1'765 lx @10°; 529 lx @20° - (profile - 20°-40°) 587 lx @20°; 128 lx @40° - (wash 25°-50°) 186 lx @25°; 69 lx @50° - (wash 15°-30°) 403 lx @15°; 151 lx @30° lx @5 m
- CRI: 2700K: >96; 5600K: >96
- R9: 2700K: >87; 5600K: >90
- TLCI: 2700K: >96; 5600K: >97
- TM30 Rf: 2700K: >96; 5600K: >92
- TM30 Rg: 2700K: <101; 5600K: <99
- Source life expectancy: > 50.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

- Zoom: (wash lens - optional) 15° ~ 30° or 25° ~ 50° - (profile lens - optional) 10° ~ 20° or 20° ~ 40° or fix 8°
- Other: 360° lens rotation - shutter blades lockable - optional 360° rotating barndoors and gel frame holder
- Other: (profile lens - optional) manual rotating gobo holder size E, outer: 37 mm - image: 23 mm - thickness: max 3 mm

COLOUR SYSTEM

- Colour mixing: warm white + cold white - tunable white
- CCT: linear CCT control

DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer
- Static mode: selection of static dimmer
- Manual mode: manual adjustment of dimmer and strobe
- Auto mode: built-in programs with execution speed adjustment

BODY

- Hardware on-board: lockable tilt with screw
- Body: aluminium die-casting
- Body colour: RAL 9004 or RAL 9010
- Other: cable not included - Cable diameter range: 6 - 10 mm

CONTROL

- Protocols: Local Knob, DMX, DALI Type6, RDM
- DMX channels: 1 / 2 / 3 / 4 channel
- RDM: RDM for remote monitoring and settings
- Display: user interface through DATAMASTER external coder (not included)
- Firmware upgrade: yes, via USB - DMX interface (UPBOXPRO/UPBOX1) not included

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 33 W
- Power factor: > 0,93
- Inrush current: 230VAC/5.7A, 110VAC/6.3A

PHYSICAL

- Operating Temperature: -10° ~ +45°
- IP rating: 20
- Cooling: passive cooling and fan-free
- Suspension and fixing: track / hanging / ceiling installation
- Data connection: screw terminal blocks
- Power connection: screw terminal blocks
- Dimensions (WxHxD): 141x200x150 mm
- Weight: 1,5 kg

CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM, cTUVus, FCC


ACCESSORIES & RELATED PRODUCTS

▪ ECLDISPPRL08B/W	Fix Profile 8° Lens, with 4 framing shutters, for EclDisplay, black/white housing	▪ ECLDISPLOUVREB/W	Anti-glare louvre for EclDisplay, black/white housing
▪ ECLDISPPRHDL18B/W	18° High definition profile lenses for Ecl Display series, black/white housing	▪ ECLDISPBDNFFB/W	Barndoor and filter frame (compatible with Wash Lenses) for EclDisplay, black/white housing
▪ ECLDISPPRHDL36B/W	36° High definition profile lenses for Ecl Display series, black/white housing	▪ ECLDISPGOBOHINDB/W	Gobo holder for EclDisplay with manual index gear on board, black/white housing
▪ ECLDISPPRHDL50B/W	50° High definition profile lenses for Ecl Display series, black/white housing	▪ ECLDISPFSNOOTB/W	Full Snoot for EclDisplay, black/white housing
▪ ECLDISPPHDZL2040B/W	20° - 40° Zoomable High definition profile lenses for Ecl Display series, black/white housing	▪ ECLDISPCEILFLGB/W	Black flange to complete the EclDisplay ceiling adapter kit, black/white housing
▪ EDISPDRVUNDATCAS	Additional optional driver for ECLDISPLAY	▪ ECLDISPCEILKIT	Ceiling adapter kit for EclDisplay (without flange)
▪ ECLDISPWASHL1530B/W	Zoomable Wash Lens 15-30° for EclDisplay, black/white housing	▪ UPBOX1UP5	Firmware uploader kit, USB IN, 5p XLR DMX OUT, DMX OUT
▪ ECLDISPWASHL2550B/W	Zoomable Wash Lens 25-50° for EclDisplay, black/white housing	▪ UPBOXPRO	Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector
▪ ECLDISPPRZL2040B/W	Zoomable Profile Lens 20-40°, with 4 framing shutters, for EclDisplay, black/white housing	▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
▪ ECLDISPHSNOOTB/W	Half Snoot for EclDisplay, black/white housing	▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm,


PRESET FULL ON 2,700K

Beam angle 50%: 7.8°

Profile Lens 8°



TECHICAL DRAWINGS



CERTIFICATIONS / APPROVALS



Conforms to UL STD. 1573
 Certified to CSA STD: C22.2 NO. 166

Visit our website
 for specifications and
 tech documentations

